



Dyn-O-Wrap



Dyn-O-Wrap is a self-adhesive film which can protect uninstalled duct sections from the intrusion of contaminants. While duct is handled, stored, or transported its interior is unprotected from water, dust and debris. Dyn-O-Wrap applied over the openings will securely seal the duct and block this exposure. With adhesion strong enough to resist separating from the duct during transportation, the film is easily removed when necessary without leaving any residue. Dyn-O-Wrap is 40% thicker than most other wraps on the market and the extra thickness ensures greater puncture resistance and durability.

FEATURES

- 40% thicker than most other duct wrapping films
 - Durable and puncture resistant
 - Self-adhesive inner surface
 - Excellent adhesion to ductwork
- Easily removable without leaving residue
 - Tinted blue for high visibility

SPECIFICATIONS

• Application: Galvanized Steel, Stainless Steel, Aluminum	• Color: Blue
• Tensile Strength: Minimum 10 psi	• Thickness: 3 mil
• Elongation: Twice its original length	• Disposal: Recyclable
• Weathering: UV resistant and waterproof	

Ordering Information

Item #	Code	Description	Dimensions (cxw)	Weight per roll (lbs.)	Packaging
13380	DW24-200	Dyn-O-Wrap Roll 24" x 200'	24" x 200'	6	6 Rolls/Box
13384	DW36-200	Dyn-O-Wrap Roll 36" x 200'	36" x 200'	9	1 Roll/Box

Sold Per Box Only

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
 Duro Dyne Midwest Division, Fairfield, OH 513-870-6000 Fax: 513-870-6005
 Duro Dyne West Division, Santa Fe Springs, CA 562-926-1774 Fax: 562-926-5778
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
 www.durodyne.com E-mail: durodyne@durodyne.com



© 2007 Duro Dyne Corp.
Printed in USA 09/07



Technical Data Sheet

20L60 Blue Duct Film Protection, Medium Tack Protection Film

Product Description:

This product is a temporary protective mask designed for use on duct, cultured marble, polished metals and similar surfaces. It provides excellent protection for natural stone and high pressure laminates. The 20L60 product is available in clear, blue and red LDPE film with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup. Meets all LEEDS Specifications no VOC's

Product Properties / Characteristics:

Nominal Results

Adhesion to Steel:
PSTC I (oz/in)

3.5 to 7.5

Tack Level:

Medium

Tensile Strength:
PSTC 31 lb/sq in

7

Elongation (%):
PSTC 31

325

Thickness:
PSTC 33

**2 mils
(nominal)**

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. For a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.