

TRUMPF



Trumpf TruTool C 160 +Chip Clipper Slitting Shear

The TruTool C 160 with integrated chip clipper is ideal for creating notches and interior cutouts. The chip can be clipped at any point.

The machine can be pulled out of the workpiece at any time and then precisely re-inserted. The TruTool C 160 with chip clipper produces distortion-free, high quality cuts.

The work surface is protected and the clear view of the workpiece makes operation easier. With the optional parallel stop, you can precisely cut strips from 1.4 to 11.8 inches long.

The work surface is protected and the clear view of the workpiece makes operation easier. With the optional parallel stop, you can precisely cut strips from 1.4 to 11.8 inches long.



C 160 + Chip Clipper Slitting Shear

<u>Specifications</u>	<u>C 160 w/Chip Clipper</u>
Cutter (further cutters available)	For 0.04 - 0.06 in. thick
Max. sheet thickness	
Steel 400 N / mm ²	16 ga.
Steel 600 N / mm ²	18 ga.
Aluminium 250 N / mm ²	14 ga.
Working speed	236"-393"/min
Start hole diameter	.59"
Smallest radius	3.5"
Rated input power	350 W
Motor capacity	
Strokes at nominal load	4200 1/min
Weight (electrical version: without cable, cordless version: with battery)	3 lbs

TRUMPF



Trumpf TruTool C 250 +Chip Clipper Slitting Shear

The TruTool C 250 with integrated chip clipper for one handed operation, has a particularly important and unique advantage. The chip can be conveniently removed at any point with one hand. The tool can be easily pulled out and accurately replaced in the workpiece, thanks to visible position markings on the cutter head. By selecting TruTool C 250 you have chosen the most powerful and fastest slitting shear in its class. It delivers the power to cut sheets up to 0.1 inch thick. The chip forms a spiral which protects the sheet surface.



C 250 + Chip Clipper Slitting Shear

<u>Specifications</u>	<u>C 250 w/Chip Clipper</u>
Cutter (further cutters available)	For 0.06 - 0.1 in. thick
Max. sheet thickness	
Steel 400 N / mm ²	12 ga.
Steel 600 N / mm ²	16 ga.
Aluminium 250 N / mm ²	12 ga.
Working speed	118"-393"/min
Start hole diameter	.86"
Smallest radius	5.9"
Rated input power	500 W
Motor capacity	
Strokes at nominal load	2400 1/min
Weight (electrical version: without cable, cordless version: with battery)	4.4 lbs