

## UV RESISTANT LINE SET TAPE

### TYPICAL APPLICATIONS

- For taping HVAC line sets
- Used on outdoor HVAC components

### ADVANTAGES AND BENEFITS

- UV Resistant
- Economical
- Easy unwind
- May be applied in a variety of temperature ranges and used in humid conditions

### CONSTRUCTION

Overall Grade/Function: UV Resistant  
Backing: UV black with white print film  
Adhesive: Acrylic

### COLOR(S)

 Black Printed (BPT)

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	37 lbs/in width	64.8 N/10 mm
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Thickness	2.85 mils	0.07 mm
Elongation	180%	180%
Service Temperature Range	-35 F to 210 F	-37 C to 99 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

US Green Building Council – LEED® Point contributor product

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 24 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

