

## OPEN WEAVE FIBERGLASS MESH

### TYPICAL APPLICATIONS

- Reinforce joints, seams, connections when paint-on mastic is used in HVAC applications.
- Apply to drywall seams before the application of joint compound

### ADVANTAGES AND BENEFITS

- Light adhesive on one side for non-slipping
- Width selection provides ample support for mastic coat
- Fabric count – 8 ends by 8 picks for superior strength

### CONSTRUCTION

Overall Grade/Function: Professional  
Backing: Fiberglass mesh  
Adhesive: Water-based acrylic

### COLOR(S)

White (WHI)



### STANDARD DIMENSION(S)

3 in x 150 ft      48 mm x 300 ft

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	75.5 lbs/in width	132.2 N/10 mm
Adhesion to Stainless Steel	8 oz/in width	0.88 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	3.83%	3.83%
Total Weight	2.75 oz/yd	65 g/m <sup>2</sup>

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-MJ-100-10/28/2013