

<b>Autobrake 2000 Series</b>	<b>AB1016</b>
<b>Bending Capacity (Mild Steel)</b>	16ga / 1,6mm
<b>Bending Capacity (Stainless)</b>	20ga / 1,0mm
<b>Bending Length</b>	122 in / 3100mm
<b>Bending Bars</b>	0.787 in / 20mm and 0.390 / 10mm / 0.250 in / 7mm
<b>Back gauge Depth (Standard)</b>	39.37 in / 1000 mm
<b>Back gauge Depth Increased (Optional)</b>	On Request
<b>Clamping Beam Opening Height</b>	4.5 in / 114mm
<b>Clamping Beam Straight Bar Tooling</b>	30°
<b>Folding Beam Adjustment</b>	2 in / 50mm
<b>Crowning of the Folding Beam</b>	5-Point 0"-0.030" Adjustment
<b>Working Height</b>	35 in / 889mm
<b>Machine Length</b>	155 in / 3935mm
<b>Machine Width</b>	56 in / 1421mm
<b>Machine Height</b>	60 in / 1522mm
<b>Machine Weight</b>	6,202 lbs. / 2,819kg
<b>Shipping Weight</b>	6,912 lbs. / 3,142kg
<b>Back Gauge Servo Motor</b>	¾ hp
<b>Clamping Beam Motor</b>	1.5 hp / 1.1kw
<b>Bending Beam Motor</b>	1.5 hp / 1.1kw