

Duro Loop Cable Sling

The Duro Loop Cable Sling enhances the Dyna-Tite suspension system by the addition of a pre-looped cable end. Once the wire rope is pulled around the anchor point and through the looped end of the cable, it is already secured at one end, saving time at the jobsite. The remaining wire rope “drop” is passed through a channel in the Dyna-Tite Cable Lock. Then, the wire rope is either wrapped around the ductwork or inserted through a fastening point and back up into the second channel of the same cable lock. The locking teeth inside the cable lock engage the wire rope which secures the ductwork in place.



To ensure maximum safety, use only looped wire rope supplied by Duro Dyne with Dyna-Tite cable locks.



Item #	Code	Description	For Use With Cable Lock	Safe Working Load* +	Quantity
30228	LC05WC3	WC3-CL12 Wire Rope X 5 ft. 1-1/2 in. Looped Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10 bags of 10
30229	LC10WC3	WC3-CL12 Wire Rope X 10 ft. 1-1/2 in. Looped Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10 bags of 10
30230	LC15WC3	WC3-CL12 Wire Rope X 15 ft. 1-1/2 in. Looped Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10 bags of 10
30232	LC25WC3	WC3-CL12 Wire Rope X 25 ft. 1-1/2 in. Looped Cable	CL12-WC3	25-150 lbs. (12-68 kg)	5 bags of 10
30233	LC05WC4	WC4-CL18 Wire Rope X 5 ft. 3 in. Looped Cable	CL18-WC4	25-250 lbs. (12-114 kg)	10 bags of 10
30234	LC10WC4	WC4-CL18 Wire Rope X 10 ft. 3 in. Looped Cable	CL18-WC4	25-250 lbs. (12-114 kg)	10 bags of 10
30235	LC15WC4	WC4-CL18 Wire Rope X 15 ft. 3 in. Looped Cable	CL18-WC4	25-250 lbs. (12-114 kg)	10 bags of 10
30237	LC25WC4	WC4-CL18 Wire Rope X 25 ft. 3 in. Looped Cable	CL18-WC4	25-250 lbs. (12-114 kg)	5 bags of 10
* Safe Working Loads are based on a 5:1 Safety Factor.					
+ Hanging at angles will reduce the Safe Working Loads. Please see our 'Effects of Hanging at Angles' table on page 18.					