



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013

**W.F. WELLS MODEL W-9-1**

**Specifications**

Capacity.....	Rectangular at 90° 9" High x 17" Wide, Round at 90° 9" Dia. Rectangular at 45° 9" High X 8" Wide, Round at 45° 8" Dia.	
Weight Capacity.....	2,000 lbs	
Blade Speed.....	70-380 SFPM	
Blade Size.....	1" X .035" X 11'-6"	
Sawing Feed.....	Variable, Hydraulic	
Blade Guide.....	Carbide with Backup Rollers	
Blade Tension.....	Manual	
Bandwheel Size.....	14½"	
Vise.....	Manual	
Blade Drive.....	3HP, 3ph, 1½ HP, 1ph	<b><u>Voltage</u></b> 230-60-1
Sawing Force.....	30-120 lbs	208-60-3
Coolant Capacity.....	10 Gallons	230-60-3
Hydraulic Capacity.....	¾ Gallon Capacity	460-60-3
Hydraulic Drive.....	⅓ HP Motor	575-60-3 (2hp)
Work Height.....	26"	
Shipping Weight.....	990 lbs	
Machine Dimensions.....	81" Length x 43" Width x 63" Height	
Electrics.....	Wired to NFPA 79 Machine Tool Standards	

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

- Casters (changes work height to 29-1/2")
- Automatic Length Stop Assembly
- Discharge Table, 20" W x 48" L (with Length Stop Assy)
- Work Light, Wired In
- Blade Tension Indicator
- Manual Air Vise
- Air Holddown
- Air Vise/Holddown Combined
- Blade Break/Stall Switch
- Stock Stand, 6" Roller
- Stock Stand, 12" Roller
- AC Vector Drive
- Free Standing Roller Stock Conveyors, 6" Centers:
  - 18" X 5' X 2,500 lbs Cap. Distributed Weight
  - 18" X 10' X 5,000 lbs Cap. Distributed Weight

For Automatics see W-914A-CNC

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

