

WATER BASED INSULATION ADHESIVES

IMPORTANT! STIR WATER BASED ADHESIVES WELL BEFORE USE!

Especially in colder climates, to prevent spraypump from clogging due to material settling.

WIT



Adhesive for bonding insulation material to sheet metal.

- **Water based**
- **Good wet tack**
- **Non-flammable when wet**

ITEM#	CODE	DESCRIPTION
5056	WIT-1	WIT - 1 Gallon Pail
5057	WIT-5	WIT - 5 Gallon Pail
5058	WIT-55	WIT - 55 Gallon Drum

PROPERTIES	
TYPE	Resin Emulsion
SOLIDS	57+ _ 2%
WEIGHT	9.8 lbs./gal.
COLOR	White
ODOR	Bland
VISCOSITY	1600-1800 CPS. Typical at 1800. Brookfield LVF #4 Spindle, 6 RPM @ 25°C
FLAMMABILITY	Non Flammable
EFFECT OF FREEZING	No Damage-1 cycle
STORAGE LIFE	6 months @ 70°F
CLEAN WITH	warm water/detergent
METHOD OF APPLICATION:	Designed for use with spray equipment or Duro Dyne Roto Bonder. As a general practice, it is advisable that liquid products be stirred prior to use.