

The Beam Clamp is a structual attachment to the top or bottom of metal I-beams, purlins, channel, or angle iron. It comes in both a large or small mouth and an Electro-Galvanized or plain finish. It is available for 3/8" and 1/2" threaded rod.

FEATURES:

- Hardended steel Cup Point Set screw.
- Complies with:

<u>Cast Clamps</u>: Federal Specification A-A-1192A (Type 19) and MSS SP-69 (Type 19).

Stamped Clamps: Federal Specification A-A-1192A (Type 23) and MSS SP-69 (Type 23).

- Maximum Load Limits: <u>Small mouth 3/8 in:</u> max top load= 500lbs max bottom load=250lbs <u>Small mouth 1/2 in:</u> max top load=950lbs max bottom load=760lbs <u>Large mouth 3/8 in:</u> max top load=500lbs max bottom load=250lbs <u>Steel C clamp 3/8 in:</u> max load=400lbs
- Designed to provide attachment of various hanger rods to structural members without drilling or welding
- UL Listed and FM approved.

Ordering Information			
Item #	Code	Description	Quantity
13185	CC38N	3/8in Plated Stamped C-Clamp w/ Lock Nut	100/box
13188	BC38NS	3/8in Plated Small Mouth Cast Beam-Clamp w/ Lock Nut	100/box
13189	BC12NS	1/2in Plated Small Mouth Cast Beam-Clamp w/ Lock Nut	50/box
13191	BC38NL	3/8in Plated Large Mouth Cast Beam-Clamp w/ Lock Nut	100/box

Duro Dyne East Division, Bay Shore, NY Duro Dyne Midwest Division, Fairfield, OH Duro Dyne West Division, Fontana, CA Duro Dyne Canada, Lachine, Quebec, Canada www.durodyne.com E-mail: (

NY 631-249-9000 Fax: 631-249-8346 d, OH 513-870-6000 Fax: 513-870-6005 562-926-1774 Fax: 562-926-5778 Canada 514-422-9760 Fax: 514-636-0328 E-mail: durodyne@durodyne.com

