



## Dual Dyn-O-Claw™



Ductwork is often reinforced with conduit to minimize movement caused by positive or negative pressures. These conduits can twist inside the duct during transit or installation. The Dual Dyn-O-Claw is designed to join the cross section of conduits to immobilize them which further strengthens the duct. The Dual Dyn-O-Claw also eliminates any vibration or rattling sound of crossing conduit. Working in conjunction with Dyn-O-Mate Rod Locks and conduit, the Dual Dyn-O-Claw creates an effective duct strengthening system and are easier and faster than other alternatives such as ties or welding. The Dual Dyn-O-Claw works for both 1/2in and 3/4in conduit.

### FEATURES

- Works for both 1/2" and 3/4" conduit
- Manufactured from 14 gauge galvanized steel
- Steel bolt secures the Dyn-O-Claw onto the Conduit

### Ordering Information

Item #	Code	Description	Quantity	Weight (lbs.)
21298	DOMOC1234	Dual Dyn-O-Claw 1/2in & 3/4in	250/box	53.75 lbs.

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346  
 Duro Dyne Midwest Division, Hamilton, OH 513-870-6000 Fax: 513-870-6005  
 Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778  
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328  
 www.durodyne.com E-mail: durodyne@durodyne.com



© 2017 Duro Dyne Corp.  
 Printed in USA 10/3/17  
 BF013429