



Technical Data Sheet

20L60 Blue Duct Film Protection, Medium Tack Protection Film

Product Description:

This product is a temporary protective mask designed for use on duct, cultured marble, polished metals and similar surfaces. It provides excellent protection for natural stone and high pressure laminates. The 20L60 product is available in clear, blue and red LDPE film with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup. Meets all LEEDS Specifications no VOC's

Product Properties / Characteristics:

Nominal Results

Adhesion to Steel:
PSTC I (oz/in)

3.5 to 7.5

Tack Level:

Medium

Tensile Strength:
PSTC 31 lb/sq in

7

Elongation (%):
PSTC 31

325

Thickness:
PSTC 33

**2 mils
(nominal)**

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

Limitations of Warranty: Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. For a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.