

SUBMITTAL RECORD

JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____



**Submittal Form
 VDS, SVDS, NS
 Hanging Strap**

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development. For maximum strength: put the two ends together and fold it over before securing to the ceiling or joist.



	VINYL DURO STRAP	NOVA STRAP
FLAME SPREAD & SMOKE DEVELOPMENT:	N/A	Less Than 25 / Less Than 50 ASTME 84
TENSILE STRENGTH:	Warp-70 lbs./In. Fill-70 lbs./In	Warp-70 lbs./In.; Fill-70 lbs./In
HEAT RESISTANCE:	200° F	200° F
TEAR STRENGTH:	Warp- 8 lbs./In. Fill-11 lbs./In	N/A
FABRIC:	Black vinyl coated polyester fill	Black Woven Polypropylene
TOTAL FABRIC THICKNESS:	.022" Approx.	.025" Approx.
QUANTITY PER CARTON:	10 rolls (Conveniently packaged in a dispenser box with cutting blade)	24 rolls per box
ADDITIONAL INFO:	N/A	Resistant to Grease, Oil, Gasoline and Acid.

HANGING STRAP			
ITEM#	MODEL	DESCRIPTION	SIZE
10190	VDS200	Vinyl Duro Strap	1-1/2" x 200'
10179	SVDS300	Single Sided Vinyl Duro Strap	1-1/2" x 300'
10180	NS300	Nova Strap	1-3/4" x 300'

Best Installation Practices

The Air Duct Council recommends supporting flex duct at manufacturers recommended intervals or no greater than 4'. Maximum centerline sag shall be no more than 1/2" per foot. Hanging Strap must be a minimum of 1-1/2" wide. For more information, please visit the Air Duct Council "Supporting Flexible Duct" section 4.6.

Duro Dyne East Division, Bay Shore, NY
 Duro Dyne Midwest Division, Hamilton, OH
 Duro Dyne West Division, Fontana, CA
 Duro Dyne Canada, Lachine, Quebec, Canada

631-249-9000 Fax: 631-249-8346
 513-870-6000 Fax: 513-870-6005
 562-926-1774 Fax: 562-926-5778
 514-422-9760 Fax: 514-636-0328

www.durodyne.com E-mail: durodyne@durodyne.com



©2019 Duro Dyne Corporation
 Printed in USA 3/19
 BO008457