

Conklin Metal Industries

Spec Sheet: Perforated

- IPA Number: 110
- Perforations: 3/32"
- Centers: 3/16"
- Open Area: 23%
- Width Direction: .500
- Length Direction: .435

Prime, Domestic, Galvanized as per ASTM A653, CS Type B Perforated 3/32" round holes on 3/16" staggered centers 23% open area 33 holes per square inch

THICKNESS	HOL E	PITC H	Aperture	MATERIAL
(mm)	(mm)	(mm)	(%)	
0.4	0.5	1	22.67	SS
0.5	3	5	32.65	Gl
0.7	0.8	2	14.51	SS
0.7	3	5	32.65	GI,SS
0.9	3	5	32.65	SS
1.0	1	2	22.67	GI,SS
1.0	1.5	3	22.67	SS
1.0	2	3.5	29.61	GI,SS
1.0	3	5	32.65	GI,SS
1.0	5	8	35.43	GI,SS
1.0	6	9	40.31	GI,SS
1.0	8	12	40.31	GI,SS
1.0	10	15	40.31	GI,SS
1.2	3	5	32.65	GI,SS
1.2	5	8	35.43	GI,SS
1.2	6	9	40.31	GI,SS
1.2	8	12	40.31	GI,SS
1.5	2	3.5	29.61	GI,SS
1.5	3	5	32.65	GI,SS
1.5	5	8	35.43	GI,SS
1.5	8	12	40.31	GI,SS
1.5	10	15	40.31	GI,SS
2.0	2	4	22,67	GI,SS
2.0	3	5	32.65	GI,SS
2.0	5	8	35.43	GI,SS
2.0	6	9	40.31	GI,SS
2.0	8	12	40.31	GI,SS
2.0	10	15	40.31	GI,SS
2.0	13	18	47.31	GI
3.0	3	5	32.65	GI,SS
3.0	5	8	35.43	GI,SS
3.0	6	9	40.31	GI,SS
3.0	8	12	40.31	GI,SS
3.0	10	15	40.31	GI,SS

SS - Stainless Steel GI - Galavanised

Atlanta, GA • Austell, GA • Greenville, SC • Birmingham, AL • Orlando, FL • Mobile, AL Memphis, TN • New Orleans, LA • Nashville, TN • Jackson, MS • Norcross, GA • Miami, FL

www.conklinmetal.com