



# TruTool TF 350

Power fasteners

## Technical data

	<b>TruTool TF 350 without tool</b>	<b>TruTool TF 350 with tilting arm</b>	
<b>MAXIMUM SHEET THICKNESSES</b>			
MAXIMUM SHEET THICKNESS, STEEL UP TO 400 N/MM <sup>2</sup>	3.5 mm	3.5 mm	.138"
MAXIMUM SHEET THICKNESS, STEEL UP TO 600 N/MM <sup>2</sup>	2.5 mm	2.5 mm	.098"
MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup>	4 mm	4 mm	.157"
<b>GENERAL</b>			
MINIMUM SHEET THICKNESS	0.8 mm	0.8 mm	.031"
MAXIMUM JOINING FORCE	25 kN	25 kN	<b>5620 LBS FORCE</b>
MAX. STROKE RATE	2 1/s	2 1/s	
MIN. EDGE SPACING	8 mm	8 mm	.314"
MAX. EDGE SPACING	58 mm	58 mm	<b>2.283"</b>
MAXIMUM FLANGE HEIGHT (B)	36 mm	36 mm	<b>1.417"</b>
NOMINAL POWER CONSUMPTION	1400 W	1400 W	
<b>WEIGHT</b>			
WEIGHT WITHOUT CABLE	8.3 kg	8.3 kg	<b>18.3 LBS</b>

Subject to changes. The details in our offer and order confirmation are definitive.