



PRO1 SUBMITTAL SHEET

Job Name: _____ Location: _____ Date: _____

Purchaser: _____ Installer: _____

Submitted to: _____ For: RNC R&R Commercial

MODEL T955WH

Wireless Universal

Up to 2 Heat 2 Cool Conventional

Up to 3 Heat 2 Cool Heat Pump

Battery or Hardwire

7 Day - 5/1/1 or Non-Programmable

This model features:

- Pre OCC Fan Purge
- Occupied/Unoccupied Programming
- Equipment Check/ Change Reminders
- 5 Year Warranty
- Humidity Control
- Light Commercial settings
- Keypad lockout
- Set dual fuel balance points (requires RZ250W)
- Connects up to 4 indoor remotes (RZ251W) for averaging or priority control
- Connect to outdoor sensor (RZ250W)
- Separate heating and cooling swing (cycle rate) adjustments
- Heating and cooling setpoint limits
- Touchscreen



Specifications:

Frequency	916 MHZ
Application/Stages	Up to 2 heat, 2 cool conventional / Up to 3 heat, 2 cool heat pump
Programmability	7 day, 5-1-1 or Non-Programmable
Changeover	Auto or Manual
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	Rc, Rh, C, Y, Y2, W/E, W2, G, B, O, H, D
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	32°F to +105°F (0°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions (Stat)	4.7"W x 4.4"H x 1.1"D (119mm W x 112mm H x 28mm D)
Dimensions (Module)	4.4" x 4.4" x 1.1"D
Warranty	5 year warranty
Switch Positions (System)	Heat / Off / Cool / Auto / Em. Heat
Switch Systems (Fan)	On / Auto
Color	White
Switch Type	Relay
Elec. Connections	Screw Terminals
Display Size	13 sq. Inches