



RAYCHEM

WinterGard, WinterGard Plus, WinterGard Wet

Selection Guide (for Pipe Freeze Protection Applications)


nVent RAYCHEM WinterGard self-regulating heating cables provide convenient, reliable freeze protection for a wide variety of professionally installed residential and commercial water-pipe and roof-and-gutter de-icing applications in nonhazardous areas. This selection guide is designed to assist in cable and accessory selection and basic circuit design of pipe-freeze-prevention applications.

Complete design guidelines, installation instructions, and safety

Construction

information are provided in the Residential & Light Commercial Self-Regulating Heating Products Application and Design Guide (H53585), the H900 Power Connection Kit (H53665), and the H908 Plug-in Power Connection Kit (H54789).

For detailed information on roof and gutter de-icing applications, please refer to the WinterGard Wet Roof & Gutter De-Icing Design, Installation and Maintenance Guide (H56804).



Pipe Applications

| | |
|---|----------------|
| Water pipes in dry areas: | H311/H611/H621 |
| Water pipes in wet areas and refrigeration condensate drains: | H612/H622 |

nVent RAYCHEM Product Specifications and Data

| | WinterGard | WinterGard Plus | WinterGard Plus | WinterGard Wet | WinterGard Wet |
|--|--|-----------------|-----------------|---------------------|----------------|
| | H311100 | H611050 | H621050 | H612050 | H622050 |
| | H311250 | H611250 | H621250 | H612250 | H622250 |
| | | | | H612500 | H622500 |
| | | | | H6121000 | H6221000 |
| Service voltage | 120 V | 120 V | 240 V | 120 V | 240 V |
| Power output at 40°F (W/ft) | 3 | 6 | 6 | 6 | 6 |
| Power output in refrigeration condensate drains at 32°F (W/ft) | n/a | n/a | n/a | 8 | 8 |
| Weight per 100 ft (lb) | 6 | 6 | 6 | 7 | 7 |
| Nom. cable width (in) | 0.380 | 0.380 | 0.380 | 0.415 | 0.415 |
| Nom. cable thickness (in) | 0.180 | 0.180 | 0.180 | 0.215 | 0.215 |
| Bus wire gauge (AWG) | 16 | 16 | 16 | 16 | 16 |
| Braid wire gauge equivalent (AWG) | 14 | 14 | 14 | 14 | 14 |
| Insulating jacket type | Modified polyolefin | | | | |
| Outer jacket type | n/a | n/a | n/a | Modified polyolefin | |
| Maximum exposure temp. (°F) | 150 | 150 | 150 | 150 | 150 |
| Environment | Use only in ordinary (nonhazardous) areas. Do not expose to any chemicals. | | | | |
| Agency approvals* | 1, 3 | 1, 3 | 1, 3 | 1, 2, 3 | 1, 2, 3 |

*1 = UL System Listed 718K Pipe Heating Cable; 2 = UL System Listed 877Z De-Icing and Snow Melting Equipment; 3 = CSA Certified LR21133

⚠ WARNING:

WinterGard systems must be installed correctly to ensure proper operation and to prevent shock or fire. Carefully read and follow the Residential & Light Commercial Self-Regulating Heating Products Application and Design Guide and the H900 series connection kit installation instructions.

- Use only in ordinary (nonhazardous) areas. Do not expose to any chemicals, oil or grease.
- In wet areas, use only WinterGard Wet.

- To minimize the danger of fire from sustained electrical arcing if the heating cable is damaged or improperly installed, and to comply with the requirements of nVent, agency approvals, and national electrical codes, ground-fault equipment protection must be used on each heating cable branch circuit. Arcing may not be stopped by conventional circuit protection.

- This selection guide does not take the place of the installation instructions included in the Residential & Light Commercial Self-Regulating Heating Products Application and Design Guide and in the H900 series accessory kits.
- System approvals and performance are based on the use of only H900 series accessories with WinterGard heating cables. These accessories must be used. Do not substitute parts.

Selection Tables

Use one of the tables below to help select the correct WinterGard heating cable for your application. (Consult the Residential & Light Commercial Application and Design Guide or H900/H908 Installation Instructions for complete system design information.)

Use Table 1 to select heating cables for insulated metal pipes. Use Table 2 for insulated plastic pipes.

Read across the table to find your pipe diameter, then drop down to the line corresponding to the lowest air temperature for that application and the correct insulation thickness. The cell at that intersection has a particular shade and may have a number.

The shade indicates which heating cable to use (key to the shades appears to the left of Table 1). A number in the cell represents the spiraling ratio (feet of heating cable per foot

of pipe). If no number appears in the cell, straight trace the pipe. If a number does appear in the cell, spiral trace the pipe. If your spiraling ratio is 2.0, multiple-trace the pipe using two straight traces at the 4 o'clock and 8 o'clock positions.

If your spiraling ratio is 3.0, multiple-trace the pipe using three straight traces at the 11 o'clock or 1 o'clock position and at the 4 o'clock and 8 o'clock positions.

Key to Tables 1 and 2

- H311 WinterGard
- H611/621 WinterGard Plus
H612/H622 WinterGard Wet
- Increase insulation thickness.

Table 1. For metal pipes with fiberglass insulation or equivalent (based on 40°F maintain)

| Lowest air temp. | Insulation thickness | Pipe diameter (inches) | | | | | | | | | | |
|------------------|----------------------|------------------------|------|------|------|------|------|------|------|------|------|-----|
| | | 0.50 | 0.75 | 1.00 | 1.25 | 1.50 | 2.00 | 2.50 | 3.00 | 4.00 | 6.00 | |
| 0°F | 0.5 in | | | | | | | | | | 1.3 | 1.8 |
| | 1.0 in | | | | | | | | | | | |
| | 1.5 in | | | | | | | | | | | |
| -20°F | 0.5 in | | | | | | | 1.1 | 1.3 | 1.5 | 1.8 | 3.0 |
| | 1.0 in | | | | | | | | | | 1.1 | 1.5 |
| | 1.5 in | | | | | | | | | | | 1.1 |
| | 2.0 in | | | | | | | | | | | |
| -40°F | 0.5 in | | | | 1.1 | 1.2 | 1.4 | 1.7 | 2.0 | 3.0 | | |
| | 1.0 in | | | | | | | | 1.1 | 1.4 | 1.9 | |
| | 1.5 in | | | | | | | | | | 1.4 | |
| | 2.0 in | | | | | | | | | | | 1.1 |

Table 2. For plastic pipes with fiberglass insulation or equivalent (based on 40°F maintain)

| Lowest air temp. | Insulation thickness | Pipe diameter (inches) | | | | | | | | | | |
|------------------|----------------------|------------------------|------|------|------|------|------|------|------|------|------|-----|
| | | 0.50 | 0.75 | 1.00 | 1.25 | 1.50 | 2.00 | 2.50 | 3.00 | 4.00 | 6.00 | |
| 0°F | 0.5 in | | | | | | 1.2 | 1.4 | 1.7 | 2.0 | 3.0 | |
| | 1.0 in | | | | | | | | | 1.2 | 1.6 | |
| | 1.5 in | | | | | | | | | | 1.2 | |
| -20°F | 0.5 in | | | 1.1 | 1.3 | 1.5 | 1.8 | 2.0 | 3.0 | | | |
| | 1.0 in | | | | | | 1.1 | 1.2 | 1.4 | 1.8 | 3.0 | |
| | 1.5 in | | | | | | | | 1.1 | 1.3 | 1.7 | |
| | 2.0 in | | | | | | | | | | | 1.4 |
| -40°F | 0.5 in | 1.1 | 1.1 | 1.5 | 1.8 | 2.0 | 3.0 | 3.0 | | | | |
| | 1.0 in | | | | 1.1 | 1.2 | 1.4 | 1.6 | 1.9 | 3.0 | | |
| | 1.5 in | | | | | | 1.1 | 1.2 | 1.4 | 1.7 | 3.0 | |
| | 2.0 in | | | | | | | | 1.1 | 1.3 | 1.8 | |


Example 1

Pipe = 2-inch-diameter metal
 Lowest air temperature = 0°F
 Insulation thickness = 1 inch
 Cable length and type = 1 foot of WinterGard H311 per foot of pipe

Example 2

Pipe = 2.5-inch-diameter plastic
 Lowest air temperature = -20°F
 Insulation thickness = 1 inch
 Cable length = 1.2 feet of WinterGard Plus H611, H621 or WinterGard Wet H612, H622

Typical Assembled System



nVent RAYCHEM WinterGard Accessories (for Pipe Applications)

| | |
|---------------|--|
| H900 | Power Connection (Hardwire) |
| H903 | Application Tape |
| H908 | Plug-in Power Connection Kit with ground fault |
| H910 | Splice and Tee Kit (wet or dry) |
| H912 | Gel-filled End Seal Kit (includes 2 seals) |
| AMC-F5 | Fixed Set Point Thermostat |
| AMC-1A | Adjustable Mechanical Thermostat 15F - 140F |
| EC-TS | Adjustable Electronic Thermostat 30F - 110F |



IMPORTANT: H900 series accessories must be used with WinterGard heating cables. Do not substitute parts.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nVent.com



nVent.com