

10" Abrasive Cut-Off

- Complete with 3 H.P. TEFC motor and vise (specify voltage/phase/hertz when ordering SEE CHART BELOW)10002F
- Adjustable outboard support (see page 17)109403
- Steel stand (see page 4)109100
- Work length gage109401
- Drip oiler (for cutting nonferrous materials)109501
- 10" Hi-speed steel blade109504



Specifications		
	8" MACHINE	10" MACHINE
Wheel Capacity	8" wheel	10" wheel
Arbor Shaft	1/2" arbor	5/8" arbor
Drive	Single	Dual
	Raw edge sure grip "V" belts with steel sheaves.	
Capacity	1" solid 1 1/2" pipe 10" miter saw only most 1 3/4" shapes @ 45°	1 1/2" solid 2" pipe
Motor	3 H.P. special hi-torque motor. Totally-enclosed, fan-cooled. Single phase 115/230 volt or 3 phase 230/460 volt. Others available. SPECIFY PHASE AND VOLTAGE WHEN ORDERING. SEE CHART BELOW	
Spindle Bearings	Precision sealed ball bearings. Lubricated for life.	
Safety Guards	Cut-off wheel and guards exceed safety code requirements. Improved spark arrestors to deflect sparks.	
Stop	Adjustable down stop limits depth of chop stroke.	

Shipping weight	8"	10"
MACHINES	3 phase 52 lbs. 1 phase 65 lbs.	3 phase 77 lbs. 1 phase 87 lbs.
10 WHEELS	7 lbs.	9 lbs.

VOLTAGE CODES	
0 = 115/1/60	1 = 230/1/60
2 = 208/3/60	3 = 230/3/60
4 = 380/3/50	5 = 460/3/60
7 = 575/3/60	
OTHER VOLTAGES AVAILABLE PLEASE CALL FOR INFO	

Prices and design subject to change without notice.