



DLSN

DUCT LOCK SEALANT

DLSN is designed for sealing metals and masonry surfaces without the need or requirement of a primer. It effectively blocks the infiltration of gases, dust and other contaminants and the exfiltration of conditioned air. DLSN is a gray, single-component material that is non-drying and permanently flexible. The DLSN in the 5 gallon & 52 gallon containers is a pumpable sealant and is ideal for use in automated injection systems.

FEATURES

- Single active component material
- Non-Drying
- Permanently flexible
- No need for a primer
- Non-corrosive
- Non-toxic
- Adheres to oily metal surfaces, painted and un-painted galvanized steel or aluminum
- Gray
- Conforms to ASTM D71-72
- 5 gallon & 52 gallon containers are pumpable



ITEM #	CODE	DESCRIPTION
5052	DLSN-C	Duct Lock Sealant - Cartridge
5065	DLSN-5	Duct Lock Sealant - 5 Gallon Pail
5068	DLSN-52	Duct Lock Sealant - 52 Gallon Drum

Duro Dyne Corporate Headquarters, Bay Shore, NY
631-249-9000 • Fax: 631-249-8346
Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
www.durodyne.com • E-mail: durodyne@durodyne.com

