



AERO-TACK 20 oz.

AEROSOL DUCT LINER and GENERAL PURPOSE ADHESIVE Fast Tacking • Variable Pattern • Adjustable Spray



Recommended Uses	Use AERO-TACK as an adhesive to position and hold all types of insulation to metal, fiberglass, paper and wood. May also be used to bond to a variety of different substrates.
Application	Apply AERO-TACK to clean substrate, holding container 6 to 8 inches from surface. Apply full, even coats.
Dry Time	Tack is immediate. Open time is approximately 3 -5 minutes. Fully bonded in 24 hours.
Temperature Limits	Storage and application.. 20°F to 100°F Service.....-30°F to 100°F
Color	Clear
Packaging	20 oz. (12 oz. net wt.) aerosol can
Precautions	Flammable. Contents under pressure. Use only in well-ventilated area. Keep away from heat and flame. Avoid prolonged exposure to vapor. Avoid contact with skin or eyes. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. In case of eye contact, flush thoroughly for at least 15 minutes and get medical attention.
Clean Up	Use mineral spirits or similar solvent with appropriate safety precautions.



POLYMER ADHESIVES

SEALANT SYSTEMS, INC.

www.polymeradhesives.com

501 Garrett Morris Parkway, Mineral Wells, TX 76067 (888) 721-SEAL Fax (888) 921-7325