

# NORLOK EZ CLINCH™

Norlok is connecting with RIDGID®, and providing a battery powered clinching tool that can be carried anywhere in the shop and on the jobsite.



The RIDGID logo is a registered trademark of RIDGID, Inc. in the U.S. and other countries

- Single hand operation makes it easier to clinch in tough spots
- With a 7/8" throat and 1" opening, the EZ Clinch™ can get over the flange to make your part
- Full rotation of clinching head and inline design provides new clinching capabilities
- Capable of clinching up to two layers of .050" aluminum or up to two layers of 16-gauge galvanized steel



EZ Clinch™ integrates with the RIDGID® RP 340

## INNOVATIONS IN ENGINEERING

# EZ CLINCH™



Model: 80100J  
Cycle Time: 9 cycles per minute  
Opening: 0.80"/20.2mm  
Tool Mass (Tool Only): 6.0lbs/2.73kg  
Tool Mass (Connected to RIGID RP340): 14.3lbs/6.5kg

Minimum sheet metal thickness:  
Two sheets 0.022"/0.56mm steel  
Two sheets 0.024"/0.61mm aluminum  
Maximum sheet metal thickness:  
Combined thickness 0.120"/3.0mm steel  
Combined thickness 0.090"/2.3mm aluminum

